

18

UNIVATION TECHNOLOGIES

REFERENCES

SUBJECT:

DATA BY: Jeff Blum

DATE:

PROJECT NO. 1

SUPERVISED BY

LCM Compounding: Sample 11163-18-1 BK (0.1% Irregular 1610
 Compounded approximately 20,000 lb. (0.1% Irregular 165
 Granular feedstock: (0.95% Ca St
 { BX-4606-H (0.5% 0042 Master
 Part 1 Bin 853
 (2/15/07)

codebook	descip	start	length	bin_L	bin_U	DL_L	NW_N	DEW_N	DE_38	eqB8	spread	Min	Max	Std	Min+1	DE
1343-18-377	60007gt1 ms	375007.517	400377	6,008	24,337	3.9	116,494	569,314	4.7	32.5	22.6	13,341	312,299	1,850,936	4,180,273	23.8
1362-18-805	60007gt1 ms	373007.936	605468	8,345	25,466	3.0	125,523	564,430	4.5	31.6	23.3	15,319	263,816	1,376,913	3,966,115	19.8

6.4 Rapid Creek Erosion Testing

250 Mm Pipe S. H. T.
Pc \geq 10 bars

Report No. 8262
critical pressure tested at 0° C.

Hines son Pipe 1 1/2 in. 1 1/2 in. 1 1/2 in.

Project 07-3679 Final Report

Notched Pipe Slow Crack Growth
 Per ISO 13479 80°C/2.2 bar
 Jahn-Labs Report 07-3701
 mean failure time: 36.72 hrs

Table 2: Summary of Predicted Type Test Results

Specimen ID	Specimen ID	Test Time (seconds)	Average Test Time (seconds)	Stages	SGC 10-079:1997[8] Requirement: Maximum Failure Time 165 ms
057-1885-31		4.051		SGC Failure	Pass
057-1885-52	1a-1	3.587	3.672 ± 338	SGC Failure	Pass
057-1885-53		3.320		SGC Failure	Pass

在本研究中，我們發現了多個與疾病相關的基因座，這些基因座可能在疾病的發病過程中發揮重要作用。

52 / 200

